

Please add the following new claims:

--13. (New) A set, comprising:
a battery charger, charge parameters of the battery charger being variable;
a unit including a battery to be charged;
a connection element removable from the battery charger; and
an arrangement outside the battery charger configured to automatically
determine at least one electrical parameter of a charge upon connection of the unit
to the battery charger via the connection element.

14. (New) The set according to claim 13, wherein the arrangement is
arranged in the connection element.

15. (New) The set according to claim 13, wherein the arrangement includes
at least one electronic component.

16. (New) The set according to claim 15, wherein the electronic component
includes a resistor.

17. (New) The set according to claim 14, wherein the connection element
includes a connector configured to cooperate with a complementary connector of the
battery charger, the arrangement arranged in the connector of the connection
element.

18. (New) The set according to claim 14, wherein the arrangement is
arranged in one a cable of the connection element and a connector configured to
cooperate with a complementary connector of the unit.

19. (New) The set according to claim 13, wherein the battery charger is
configured to charge a battery of a portable telephone.

20. (New) A battery charger, comprising:
an arrangement configured to vary at least one charge parameter; and
at least one input configured to receive one of an element and a signal to
determine the charge parameter.

21. (New) The battery charger according to claim 20, wherein the input includes an input of a connector configured to cooperate with a complementary connector of an element configured to connect to a unit to be charged.

22. (New) A connection element configured to connect a battery charger to a battery unit, comprising:

at least one component configured to determine in the battery charger parameters of a charge of the battery unit, the connection element removable from the battery charger.

23. (New) The connection element according to claim 22, wherein the at least one component includes at least one electronic component, terminals of the electronic component configured to connect to the battery charger via a connector of the connection element.

24. (New) The connection element according to claim 23, wherein the electronic component includes a resistor.

25. (New) A battery unit configured to connect to a battery charger through a connector, comprising:

an arrangement configured to automatically determine electrical parameters of a charge generated by the battery charger upon connection of the battery unit to the battery charger via the connector.

26. (New) The battery unit according to claim 25, wherein the arrangement includes at least one electronic component connected to a pair of terminals connectable to an electrical circuit of the battery charger, the electrical component configured to determine the charge parameters of the battery charger.

27. (New) The battery unit according to claim 26, wherein the at least one electronic component includes a plurality of electronic components.

28. (New) The battery unit according to claim 26, wherein the electronic component includes a resistor.--.